



Kent Housing Group

PAS 2035 – What's it all about?

1 October 2021

Dr Peter Rickaby

Technical Director, The Retrofit Academy
Chair, BSI Retrofit Standards Task Group
UK Centre for Moisture in Buildings, UCL

Retrofit for the Future 2010-2014

- £17 million Technology Strategy Board (Innovate UK) deep retrofit pilot programme for housing associations
- 115 houses (86 projects) retrofitted (target 17 kgCO₂/m²yr) with grants of £150k each
- Typical project cost £90k, about one third achieved the performance target, but many successful and informative projects
- Two-years post-occupancy monitoring and one year of analysis by technical panel (data publicly available)
- Results published in *Reducing energy use in existing homes: a guide to making retrofit work* (TSB 2014)



Retrofit for the Future

Key Lessons

- Coherent integration of improvements into whole-dwelling packages (fabric + services)
 - Pay attention to corners, junctions, edges and interfaces
 - Most technical risks are moisture-related
- Critical role of ventilation
 - Critical to integrity of building fabric and health of occupants
 - Poor strategies, specifications, installation and commissioning
 - Many systems not matched to fabric and did not fit
- Importance of commissioning, handover and advice
 - Occupants and maintenance staff must be engaged

“Retrofit is not rocket science – but it is complicated”


Rick Holland, Innovate UK



Retrofit Failures

- **Preston** *2013*
 - Nearly three hundred houses rendered damp and unsaleable by badly installed EWI
- **Wales** *2013*
 - Damp and mould in many village homes caused by badly installed EWI
- **Glasgow** *2014*
 - Four tonnes of EWI fell off the top storey of a residential tower
- **Edinburgh** *2014*
 - The outer leaf fell off the insulated gable wall of a school
- **Grenfell Tower** *2017*
 - 72 dead after fire spread via new insulated external cladding
- **Numerous insulation failures** *2010-2020*
 - Mostly following poor or inappropriate installation of CWI or EWI

Each Home Counts



Industry-led review

- Sponsored by BEIS and MHCLG
- Led by Peter Bonfield (BRE)
- Multiple work-streams
- Hundreds of people involved

Twenty-seven recommendations

- Consumer protection
- Advice and guidance
- Quality and standards
- Skills and Training
- Compliance and Enforcement
- Insulation and building fabric
- Smart meters
- Home energy technologies
- Social housing

Implementation

- Coordinated by a cross-industry Implementation Board
- BEIS support > £3 million

Dr Peter Bonfield, OBE, FREng



Department for
Business, Energy
& Industrial Strategy


Department for
Communities and
Local Government

December 2016


Retrofit QA - Each Home Counts

- Two strategic objectives
 - Boost demand for retrofit by restoring trust in the industry
 - Reduce risks to finance bodies, to encourage funding
- Establishes a QA framework to support the industry
 - TrustMark plus the BSI Retrofit Standards Framework
- Promotes consolidation of fragmented industry
 - Encourage adoption of business models for whole-dwelling retrofit

BSI Retrofit Standards Framework




PAS 2035



Department for Business, Energy & Industrial Strategy




PAS 2035



PAS 2035 Risk Assessment *Clause 7*

- Carried out by Retrofit Coordinator
 - Based on pre-assessment (triage) data
 - Before whole-dwelling and ventilation assessments
- Risk assessed as A, B or C
 - Depending on five criteria
 - Number of dwellings and measures, construction, built form
 - High rise and protected historic buildings are always risk C
- Assessed risk determines minimum required qualifications
 - Retrofit Assessor | Retrofit Designer
- Assessed risk determines Path through the PAS
 - Path A: Simple requirements
 - Path B: More onerous requirements
 - Path C: Much more onerous requirements

PAS 2035 Risk Assessment *Clause 7*



PAS 2035 Whole Dwelling Assessment *Clause 8*

- Wider scope than EPC or ECO assessments
 - Context
 - Setting, planning status, exposure, etc.
 - Condition
 - Structural issues, damp, mould, rot, etc
 - Occupancy
 - Including identification of vulnerable occupants
 - Energy performance
 - Collection of Full SAP or PHPP data for IOE
 - Ventilation assessment
 - To determine whether an upgrade is required
 - Significance
 - BS 7913 assessment if traditionally constructed or protected building

PAS 2035 Ventilation *Annex C*

Assessment

- Existing ventilation is inadequate if
 - Evidence of condensation or mould
 - No working ventilation system present
 - Ventilation present but incomplete (including air inlets)

Upgrade

- If insulation and/or air tightness measures are proposed, and the existing ventilation is inadequate, then
- Ventilation must be upgraded
 - If leaky (intended $Q_{50} > 5 \text{ m}^3/\text{m}^2\text{h}$) then IEV or PSV required
 - If airtight (intended $Q_{50} < 5 \text{ m}^3/\text{m}^2\text{h}$) then MEV, MVHR or PIV required
 - System capacity must be based on full occupancy
 - Demand control required to ensure energy efficiency

Establishing Intended Outcomes Clause 9 (Paths B and C)

Improvement Option Evaluation

- Identifies measures required
 - To improve dwelling for 2050
- Compares cost effectiveness
 - Using Full SAP or PHPP
- Tabular summary of options
 - Estimated capital costs
 - Cost effectiveness
 - Carbon cost effectiveness
- Basis of advice to client
 - Which measures to install?

Medium-Term Improvement Plan


- Recognises budget constraints
 - 2050 measures unaffordable
 - Work needs to be staged
- Plan for 20-30 years
 - Prioritises measures in stages
 - Usually 'fabric first' approach
 - Identifies compatibilities
 - Preserves opportunities
- Summarises intended outcomes
 - And how to get there
 - Agreed with the client

PAS 2035 Design *Clause 9*

- The scope of the retrofit design depends on the risk Path
- Irrespective of Path, all designs must:
 - Provide for the outcomes agreed with the Client
 - Be based on the whole-dwelling assessment
 - Take account of the architectural and heritage context
 - Take account of planning and building control requirements
 - Allow for the management of moisture in the building
 - Include construction details (corners, junctions and edges)
 - Consider interfaces between fabric, systems and occupants
 - Include a ventilation upgrade if required
 - Specify testing, commissioning and handover requirements
 - Specify required guarantees and warranties

PAS 2035 Measures Interaction Matrix *Annex D*

- Used in risk assessment and design
- Identifies where design must include construction details
- Identifies where design must include compatible specifications



Installation *Clauses 10-12*

- Installation of retrofit measures must comply with PAS 2030: 2019
- The PAS 2030 Retrofit Installer must work to a design that is compliant with PAS 2035
- PAS 2030 includes requirements for
 - Validating the design and preparing a method statement
 - Qualification or competence of operatives
 - Pre-installation building inspections
 - The installation process (measure-specific requirements)
 - Testing, commissioning and handover
 - Provision of guarantees and warranties
 - Record keeping

PAS 2035 Advice *Clause 13*


- Energy advice must be provided at
 - Inception
 - After improvement option evaluation (agree retrofit plan)
 - At handover
- Delivery formats
 - Inception advice may be online and generic
 - Advice after IOE delivered by Retrofit Coordinator
 - Advice at handover delivered by installer(s)

PAS 2035 Evaluation *Clause 14*

- Objectives
 - To confirm that intended outcomes have been achieved
 - To identify any unintended consequences
- Basic evaluation
 - Applies to every project (questionnaire)
 - Confirms outcomes and customer satisfaction
- Intermediate evaluation
 - Investigates poor outcomes, unintended consequences
- Advanced evaluation
 - Further investigation to understand and resolve discrepancies between predicted and actual outcomes

PAS 2035 Summary

- Retrofit Coordinator
 - Required for every project: protects customer's interests and the public interest
 - Agrees intended outcomes with client, coordinates work, ensures and claims compliance
- Risk assessment
 - Based on pre-assessment (triage) data
 - Determines the Path (A-C) through the PAS
 - Determines required qualifications for Retrofit Assessor and Retrofit Designer
- Whole-dwelling assessment
 - Includes context, condition, occupancy, energy performance, ventilation and significance
- Improvement option evaluation
 - Basis of medium-term improvement plan (Paths B and C) agreed with client
- Design
 - Requirements depend on the risk Path (A-C)
 - Additional requirements for traditionally constructed and protected buildings
 - Moisture management is integral to the design requirements
 - Ventilation upgrades required if existing is assessed as inadequate
- Installation
 - Must comply with PAS 2030: 2019
 - Includes testing, commissioning and handover
- Evaluation
 - Confirms agreed outcomes, investigates discrepancies and unintended consequences



Questions?



Kent Housing Group

PAS 2035 – What's it all about?

1 October 2021

Dr Peter Rickaby

Technical Director, The Retrofit Academy
Chair, BSI Retrofit Standards Task Group
UK Centre for Moisture in Buildings, UCL